


NVR

4/8 CH PoE NVR

8MP/6MP/5MP/4MP/3MP/1080P/720P HD PoE NVR



NGD-8204.8POE

NGD-8108.8POE



HD Output

HD IPC

DDNS

Network

PTZ

Audio

MIC

Mobile

CMS

USB

Mouse

E-mail

STD

VCA

This series of products supports 4/8 CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P high definition IP video input, which adopts the advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

This series integrates with 4/8 PoE network ports and supports 4/8 CH IPC direct connection to NVR, simultaneous 4/8 CH playback and 4K ultra high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



Specifications

Model		NGD-8204.8POE	NGD-8108.8POE
System	OS	Embedded Linux	
Video	Network Input	4 CH IPC input	8CH IPC input
	Network Input Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF	
	Output	HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA: 1920 × 1080 / 1280 × 1024 / 1024 × 768	
	Screen Display Mode	1/4	1/4 / 6/8/9
	Compression	H.265S / H.265+ / H.265 / H.264	
Audio	Network Input	4 CH IPC audio input	8 CH IPC audio input
	Local Input	RCA × 1 (for two-way audio)	
	Local Output	RCA × 1	
	Compression	G.711(U/A)	
Record	Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF	
	Frame Rate	NTSC:30fps; PAL:25fps	
Playback	Simultaneous Playback	Max. 4 CH	Max. 8 CH
	Search	Time slice / time / event / tag / smart search	
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events	
	Function	Play, pause, FF, FB, digital zoom, etc.	
Decoding Capability	Live View/ Playback	Non-AI Mode: 1×8MP@30fps/4×4MP@30fps AI Mode: 1×8MP@30fps/4×3MP@30fps	Non-AI Mode: 1×8MP@30fps/4×4MP@30fps/8×720P@30fps AI Mode: 1×8MP@30fps/4×3MP@30fps/8×720P@30fps
		Mode	Manual, sensor, motion, exception, smart events
Alarm	Input	Supports IPC alarm input	
	Output	Supports IPC alarm output	
	Triggering	Record, snap, preset, e-mail, etc.	
	Interface	RJ 45 × 1 (10/100/1000Mbps)	
Network	Protocol	TCP / IP, IPv4, IPv6, UDP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, HTTP, SMTP, HTTPs, 802.1x, RTSP, RTP, RTCP, FTP, WebSocket, SNMP, IGMP, ONVIF	
	Incoming/ Outgoing Bandwidth	80/80 (Mbps)	80/80 (Mbps)
		*When the AI function of the IPC is enabled, the actual incoming bandwidth(max.bitrate) is more than the set value in the NVR.	
	Client Connection	Max. 64 users access	
Face	Face Detection Performance (AI by IPC)	4 CH	8 CH
	Face Detection Performance (AI by Device)	2 CH (2MP) or 1 CH (4MP)	
	Face Match Performance	No	
	Statistical Graph of Information	Bar graph	
	Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period	
Perimeter Protection	Human/Vehicle Classification (AI by IPC)	4 CH	8 CH
	Human/Vehicle Classification (AI by Device)	2 CH (2MP) or 1 CH (4MP)	
Video Metadata	Human/Vehicle Attribute Analysis (AI by IPC)	Yes	
Other Functions	Fisheye	Supports fisheye dewarping via Web Client and mobile APP	
	Plate Recognition (AI by IPC)	Yes	



*AI mode: AI by device supported
Non-AI mode (default mode): AI by device not supported

Mobile Device	OS	iOS, Andriod	
Storage	HDD Interface	SATA3.0 × 1, max 10T	
Backup	Local Backup	U disk, USB mobile HDD	
	Network Backup	Yes	
Port	USB	USB 2.0 × 2	
	Remote Controller	Optional	
PoE	PoE Ports	100M RJ45 × 4	100M RJ45 × 8
	Standards	IEEE802.3AF/AT	
	Output Power	≤ 48W	≤ 72W
Others	Power Supply	DC 48V/1.25A	DC 48V/1.8A
	Consumption	≤ 10W (without HDD)	
	Dimensions (mm)	300 × 249 × 45(W × D × H)	
	Working Environment	-10 ~ 50 °C, 10% ~ 90% humidity	
	Certificate	CE, FCC	
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE	

Features


- Support 4/8 CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/DI/CIF IP video input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor / POS / AI recording
- Playback : 4 / 8CH simultaneous playback
- Search : time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Support POS information overlay on live view and playback
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- 4/8 PoE network ports; IPC can be directly connected to NVR; PoE power supply supported
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

Dimensions



Rear Panel

NGD-8204.8POE



NGD-8108.8POE

